Dotec-Audio DeeGain
User's Guide

About DeeGain
Thank you for choosing Dotec-Audio DeeGain.

DeeGain is a simple plugin which controls the volume from -20db to +20db.
Insert DeeGain between the other effect plugins, then it will work like the gain/trim control of a mixer console.

Installation on Windows OS
1. Those plug-ins are provided as a .dll and .vst3 and .aaxplugin folder（AAX）.
2. To install the plug-ins, simply copy it to your system's shared VST or VST3 or AAX folder.
   AAX folder : *C:\Program Files\Common Files\Avid\Audio\Plug-Ins*
3. If you're not sure where that is, please consult your music software's documentation.
4. If your music software is already running, you'll probably need to quit and restart if before the plugin is recognised.

Installation on MacOS
1. Those plug-ins are provided as a .vst (VST) and .component (AU) files and .aaxplugin（AAX）files.
2. To install the plug-ins, open "**install.pkg**" and follow the installer instructions.
3. If your music software is already running, you'll probably need to quit and restart before the plugin is recognised.

Panel Description

Enable/Disable Switch (Lightning Switch)
Enables/Disables DeeGain.

Level Meter
It indicates the output level (dB)

Output Fader
It will increase or decrease the output level(-20dB～+20dB)

How to Register

The DOTEC-AUDIO product becomes the "**product version**" by registering the serial key and e-mail address in the "**demo version**".
This section describes how to register the serial key you purchased.

Step 1

You can register serial key by clicking registration button.

Step 2

This window will be displayed.
Please enter a serial key and your email address in the textbox and click OK button.
* The registration requires an internet connection.