

Dotec-Audio DeeCompressor

User's Guide

About DeeCompressor

Thank you for choosing Dotec-Audio DeeCompressor.

DeeCompressor is a VST plugin with following features:

- This is a multifunctional compressor that can be used from tracks to buses.
- Filter for detection, M/S, sidechain, auto-release, and limiter are available.
- Channel link and DRY/WET can be used to create detailed sounds.
- Attack and release are creative with ultra-short time settings.
- Zero latency allows for use while composing without affecting the instrument input.

Installation on Windows OS

1. Those plug-ins are provided as a .dll and .vst3 and .aaxplugin folder (AAX).
2. To install the plug-ins, simply copy it to your system's shared VST or VST3 or AAX folder.
AAX folder : *C:\Program Files\Common Files\Avid\Audio\Plug-Ins*
3. If you're not sure where that is, please consult your music software's documentation.
4. If your music software is already running, you'll probably need to quit and restart if before the plugin is recognised.

Installation on MacOS

1. Those plug-ins are provided as a .vst (VST) and .component (AU) files and .aaxplugin (AAX) files.
2. To install the plug-ins, open “**install.pkg**” and follow the installer instructions.
3. If your music software is already running, you'll probably need to quit and restart before the plugin is recognised.

Panel Description



Enable/Disable Switch (Lightning Switch)

Enables/Disables DeeCompressor.

HPF LPF

Filters the frequency band of the sound source to be detected.

CH LINK

The higher the value, the stronger the synchronization between left and right or mid-side.

PEAK/RMS

Adjust the detection method between PEAK and RMS.

THRESHOLD

Sets the threshold level.

RATIO

Sets the compression ratio.

KNEE

The higher the value, the smoother the sound compression and the less distortion.

ATTACK

Sets the length of attack.

RELEASE

Sets the length of the release. The shorter the release, the easier it is to increase the sound pressure; the longer the release, to reduce distortion.

SIDECHAIN

Enable sidechain input.

M/S

Enable M/S input.

AUTORELEASE

Automatically adjusts the length of the release.

LIMIT

Enable Limiter.

INPUT

Adjusts the input level. Adjust the meter to -6dB as a standard.

OUTPUT

Final adjustment of the output volume.

Meters

Indicates INPUT, OUTPUT, and GR (gain reduction).

The values hold the maximum value and can be cleared with the RESET button.

How to Register

The DOTEK-AUDIO product becomes the "**product version**" by registering the serial key and e-mail address in the "**demo version**".

This section describes how to register the serial key you purchased.

Step 1



You can register serial key by clicking registration button.

Step 2

A screenshot of a 'Registration' dialog box. The title bar says 'Registration'. The text inside says 'Please enter the serial key and your e-mail address for the registration.' There are three input fields: 'Serial key', 'E-mail address', and 'E-mail address(Verify)'. Each field has a red arrow pointing to it. At the bottom, there are three buttons: 'Open the shopping page', 'Cancel', and 'OK'. The 'OK' button is highlighted with a red rectangle.

This window will be displayed.

Please enter a serial key and your email address in the textbox and click OK button.

*** The registration requires an internet connection.**